










# LOCKING SEALANTS

## CONTENTS

Picture	Description and Service Ref. No.	Manufacturers Reference	Application	Features and benefits
	Threadlocker 4101/0400	Loctite 932 Threadlocker Permabond A011	Non-permanent locking & sealing of threaded parts	<ul style="list-style-type: none"> <li>• Removable using normal tools</li> <li>• Allows even large or fragile components to be dismantled</li> </ul>
	High-strength Thread Locker 4102/0500	Loctite 275 Threadlocker Permabond A140	Permanent assembly of badly worn: <ul style="list-style-type: none"> <li>• threads</li> <li>• bearings</li> <li>• shafts</li> <li>• splines</li> <li>• keyways</li> </ul>	<ul style="list-style-type: none"> <li>• Gap filling</li> <li>• Eliminates reboring</li> <li>• Vibration proof</li> <li>• High strength</li> </ul>
	Thread Lock and Sealer 4101/0200	Loctite 242 Permabond A113	Threadlocking and sealing: <ul style="list-style-type: none"> <li>• screws</li> <li>• nuts</li> <li>• bolts</li> <li>• small hydraulic fittings</li> </ul>	<ul style="list-style-type: none"> <li>• Vibration resistant</li> <li>• Prevents corrosion</li> <li>• Can be dismantled using normal tools</li> </ul>
	High Strength Thread Lock and Sealer 4101/0500	Loctite 262 Threadlocker Permabonds A115	Locking and sealing: <ul style="list-style-type: none"> <li>• threads up to M20</li> <li>• bushes</li> <li>• bearings</li> <li>• studs</li> <li>• liners</li> <li>• splines</li> <li>• keyways</li> </ul>	<ul style="list-style-type: none"> <li>• Tolerates heavy vibration</li> <li>• Eliminates interference fits</li> <li>• Prevents corrosion</li> <li>• Can be dismantled if required</li> </ul>
	High Strength Retainer 4101/0600	Loctite 648 Permabond A118	Permanent retaining of: <ul style="list-style-type: none"> <li>• bushes</li> <li>• bearings</li> <li>• keys</li> </ul>	<ul style="list-style-type: none"> <li>• Eliminates interference fits</li> <li>• Better stress distribution increases strength</li> <li>• Vibration resistant</li> <li>• Prevents fretting</li> </ul>
	Thread Seal 4102/1900	Loctite 577 Threadsealant Permabond A1044	Pipe-sealing <ul style="list-style-type: none"> <li>• water</li> <li>• gas</li> <li>• air</li> <li>• oil</li> </ul>	<ul style="list-style-type: none"> <li>• Easy to apply</li> <li>• Instant low pressure seal</li> <li>• Allows adjustment up to 30 mins after application</li> <li>• Can be dismantled using normal tools</li> </ul>
	Gasket Seal 4102/1200	Bondloc Gasket Seal B574	Gasketing <ul style="list-style-type: none"> <li>• flanges</li> <li>• pipes</li> <li>• housings</li> </ul>	<ul style="list-style-type: none"> <li>• Does not creep shrink or relax</li> <li>• Can be used on dissimilar materials</li> <li>• Economical</li> <li>• Replaces all sizes of formed gaskets</li> </ul>
	Adhesive 4103/0900	495 Superbonder Permabond C2	General purpose super-glue for bonding	<ul style="list-style-type: none"> <li>• Very fast cure rate</li> <li>• High strength</li> <li>• Colourless</li> <li>• No mixing</li> <li>• Even bonds difficult rubbers</li> </ul>
	Cleaner & Degreaser 4104/1500	7063 Superclean Permabond Permaclean II	For general purpose cleaning	<ul style="list-style-type: none"> <li>• Prepares surfaces prior to bonding</li> <li>• Will dissolve grease</li> </ul>
	Activator 4104/0200	Loctite 747T Activator T Permabond A905	For promoting faster cure with threadlocking and sealing materials	<ul style="list-style-type: none"> <li>• Faster cure speeds</li> <li>• Enables the bonding and sealing of materials such as plastics, which cannot normally be assembled</li> </ul>